


LEDALITE - FLOATPLANE

TEST DATE:	17 Sep 2019	CATALOG NO:	24x5LSCAA04
Lamp Type:	LED	Description:	FLOATPLANE STD 4500LM 935
No. of Lamps:	176		
Rated Lamp Lumens:	-1	Flux (lm), Efficiency (%):	4525 lm 100.0%
Input Watts:	277 VAC 37.8	Up/Dn Ratio, Efficacy (lm/W):	74% Up / 26% Dn 119.7
CIE-IES Classification:	Semi-Indirect	Report:	LNG00102

CANDELA DISTRIBUTION						Flux
	0	22.5	45	67.5	90	Lumens
0	424	424	424	424	424	
5	420	422	421	421	421	40
15	403	407	404	405	402	114
25	374	378	373	374	368	172
35	332	334	326	328	322	206
45	279	281	272	272	268	212
55	214	218	208	209	204	189
65	148	152	141	142	137	143
75	80	82	73	75	70	81
85	20	24	15	14	12	21
90	0	0	0	0	0	
95	51	90	187	167	273	175
105	158	242	530	717	854	514
115	253	394	668	842	907	613
125	336	482	718	849	900	597
135	400	523	716	841	886	526
145	449	539	688	795	828	418
155	480	536	639	724	746	291
165	499	525	574	628	637	163
175	508	513	518	533	528	50
180	509	509	509	509	509	




CHARACTERISTICS			
RP1	Meets RP-1-12 recommendations for VDT-Critical spaces		
Direct: Peak Candela & Angle (0deg)	423.6	0.0	
Direct: Peak Candela & Angle (90deg)	423.6	0.0	
Spacing Criteria (0deg, 90deg, 180deg)	1.24	1.22	N/A
Indirect: Peak Candela & Angle	909.9	112.5	
Indirect: Zenith Candela, Peak to Zenith	508.6	1.79	
Luminous Length, Width, Height (ft)	3.89	0.56 0.00	
UGR (4H x 8H, 0.25H)	N/A		
Ballast Factor, Multiplication Factor	1.000	1.000	
DLC (120/277), DLC (347)	Standard	Standard	
x, y, CCT, Duv	0.4055	0.3863	3460 -0.0020
CRI (Ra), R9	93		65
120V: P(W), I(A), THD(%), PF	37.7	0.314	6.4 0.999
277V: P(W), I(A), THD(%), PF	37.8	0.140	8.3 0.978
347V: P(W), I(A), THD(%), PF	37.0	0.109	6.5 0.979

COEFFICIENTS OF UTILIZATION (%)													
Pc---	80				70				50				0
Pw---	70	50	30	10	70	50	30	50	30	10	0	0	
RCR	0	101	101	101	101	90	90	90	70	70	70	26	
	1	92	88	84	81	82	79	76	61	59	57	22	
	2	84	77	71	66	75	69	64	53	50	47	18	
	3	77	67	60	55	68	60	54	47	43	39	15	
	4	70	60	52	46	62	53	47	42	37	33	13	
	5	64	53	45	39	57	47	41	37	32	29	11	
	6	59	47	39	34	52	42	36	33	28	25	10	
	7	54	42	35	29	48	38	32	30	25	22	9	
	8	50	38	31	26	45	35	28	27	22	19	8	
	9	47	35	28	23	41	31	25	25	20	17	7	
	10	43	32	25	20	39	29	23	23	18	15	6	

*Based on a floor reflectance of 0.2

ZONAL LUMEN SUMMARY			
Zone	Lumens	%Fixture	%Lamp
0-30	326	7.2%	7.2%
0-40	532	11.8%	11.8%
0-60	933	20.6%	20.6%
0-90	1178	26.0%	26.0%
90-130	1898	42.0%	42.0%
90-150	2842	62.8%	62.8%
90-180	3347	74.0%	74.0%
0-180	4525	100.0%	100.0%

AVG LUMINANCE (cd/m ²)			
	0	45	90
0	2092	2092	2092
5	2084	2086	2089
15	2060	2067	2054
25	2040	2032	2008
35	2003	1967	1941
45	1947	1901	1869
55	1840	1795	1758
65	1734	1649	1595
75	1525	1391	1334
85	1150	861	652



LEDALITE

Ledalite
 19750 - 92A Avenue
 Langley, BC
 CANADA V1M 3B2
 Phone: 604-888-6811
 Fax: 800-665-5332
 604-888-2003