


Shine™



Recessed

2'x2'

1 TT5 (40W)



Project Name

Spec Type

Notes

Order Guide

Some combinations of product options may not be available. Consult factory for assistance with your specification.

3322

B140

Product Series & Size

Shine 2'x2'

Version

D1 Standard T-Grid
A1 Air Return on Standard T-Grid

Configuration

ST Standalone
CR Continuous Row
SMS Standalone Master/Satellite
CMS Continuous Row Master/Satellite

Lamping

1 TT5 (40W)

Housing

S Standard (22ga.)
N New York (20ga.)
C Chicago Plenum

Wiring

1 1 cct
5 1 cct w/ Battery Pack
7 1 cct Dimming

Voltage

1 120V
2 277V
3 347V

Ballast

E Standard Ballast

See details on next page

Consult website for complete list of standard wiring options

Consult website for ballast manufacturer information

Upgrades & Accessories

Please indicate with check mark.


☐ Lamps Included

☐ Lamps Included & Installed

☐ Job Pack

☐ Flex Whip

☐ Drywall Kit



Not available in continuous row

Can be mounted to wood frame or with hanger wire




Wood Frame




Hanger Wire

☐ Response Daylight
For details visit www.ledalite.com/response

Cross Section



Side View




Shine™

Recessed

2'x2'

1 TT5 (40W)



Photometry


Report Summary

Report # 9901693
Filename 3322D1B140.ies
Efficiency 83.3%

Spacing Criteria 1.19 @ 0° along
1.26 @ 90° across

Candela Distribution

Vertical Angle	Horizontal Angle					Zonal Lumens
	0	22.5	45	67.5	90	
0	1005	1005	1005	1005	1005	
5	998	1000	1000	1003	1002	98
15	954	959	964	975	975	273
25	869	884	889	905	901	411
35	738	767	773	798	795	486
45	591	620	626	675	688	492
55	417	440	449	501	501	415
65	254	281	282	308	301	284
75	117	124	124	141	137	138
85	25	26	20	22	17	29
90	0	0	0	0	0	



Coefficients of Utilization (%)

Ceiling: Wall:	80					70					50					0				
	70	50	30	10		70	50	30	10		70	50	30	10		70	50	30	10	
0 RCR	99	99	99	99		96	96	96	92	92	92	92	92	83		83	83	83	83	
1	91	87	84	81		89	85	82	82	79	77	77	71			71	71	71	71	
2	83	76	71	66		81	75	70	72	68	64	60				60	60	60	60	
3	76	67	61	56		74	66	60	64	58	54	51				51	51	51	51	
4	69	60	53	47		68	59	52	57	51	46	43				43	43	43	43	
5	64	54	46	41		62	53	46	51	45	40	38				38	38	38	38	
6	59	48	41	36		58	47	41	46	40	35	33				33	33	33	33	
7	55	44	37	32		53	43	36	42	36	31	29				29	29	29	29	
8	51	40	33	28		50	39	33	38	32	28	26				26	26	26	26	
9	48	37	30	25		46	36	30	35	29	25	23				23	23	23	23	
10	45	34	27	23		44	33	27	33	27	23	21				21	21	21	21	

Based on a floor reflectance of 0.2

Avg. Luminance (cd/m²)


Vertical Angle	Horizontal Angle		
	0	45	90
55	2122	2285	2550
65	1754	1948	2079
75	1320	1399	1545
85	837	670	569

IES files for this and other photometric options can be downloaded online at www.ledalite.com

Additional Information


Mounting

Integrates with most common T-bar ceiling types.



Flat T-Grid

Option D1 works with 9/16" and 15/16" flat T-grid ceilings.




Slot T-Grid

D1 can also be used with slot T-grid ceilings, but it will not sit flush with the bottom of the T-bar.


Ceiling Types

Integrated mounting tabs can be field-adjusted to various T-bar ceiling heights for fastening directly to the T-bar grid and/or tied-off to the building structure.



1" T-bar height
1-1/2" T-bar height
1-11/16" T-bar height

Air Return



The air return version features slotted vents along the sides of the fixture. As a result, the installation method of the air return version is different to the standard version, and the fixture cannot be installed in continuous rows.

Specifications

Due to continuing product improvements, Ledalite reserves the right to change specifications without notice.

Housing

Die-formed, post-painted, 22 gauge cold-rolled steel (New York City version is 20 gauge). Wire entrances are positioned on the side of the housing to allow easy wiring access for the installer. Multiple wire entrances are available on top or side to allow continuous row mounting of fixtures. Maintenance can be performed from below the ceiling without tools. No hardware is visible.

Weight

Maximum 23 lbs.

Optical System

Optical system consists of highly reflective painted interior reflectors and three flat acrylic lenses with 95% transmittance.

Mounting

Fixture is compatible with most ceiling types. Option D1 works with 9/16" and 15/16" standard T-grid ceiling systems. D1 can be used with slot T-grid ceiling systems but fixture will be slightly regressed above the T-bar. Integrated tabs are provided for different T-grid heights. Optional drywall kit is available for non-accessible ceilings.

Ballast

Electronic. Supplied with pre-installed ballast disconnects as per national electric codes.

Wiring

Fixtures are factory pre-wired and tested for all circuits and emergency battery packs; all leads pulled to a side access with cover plate. Optional armored cable flex whips are supplied in 6' lengths for 1x4, 2x2 and 2x4 fixtures. Armored cable flex connectors are supplied in 9' lengths for optional master/satellite configurations.

Air Return

Air return option available in 2'x2' and 2'x4' sizes. Perforated air return side rails are finished in black.

Approvals

Certified to UL & CSA Standards. City of Chicago Approved CCEA (housing option C). Designed to comply with NYC code requirements (Housing Option N).

Finish

Housing and Frame: Post-painted, high quality powder coat. Available in white.