

Shine™




Recessed

20"x2'

3 T5



Project Name

Spec Type

Notes

Order Guide

Some combinations of product options may not be available. Consult factory for assistance with your specification.

3352			F314	-		-		-		-	
Product Series & Size	Version	Configuration	Lamping	Housing	Wiring	Voltage	Ballast				
Shine 20"x2'	NN Standard T-Grid	ST Standalone	3 T5 (14W)	S Standard (22ga.)	1 1 cct 2 2 cct 5 1 cct w/ Battery Pack 7 1 cct Dimming	1 120V 2 277V 3 347V	E Standard Ballast				
					Consult website for complete list of standard wiring options						
					Consult website for ballast manufacturer information						

Upgrades & Accessories

Please indicate with check mark.

☐ Lamps Included


☐ Lamps Included & Installed

☐ Job Pack


☐ Flex Whip

☐ Response Daylight
For details visit www.ledalite.com/response

Cross Section




Side View



Shine™

Recessed
20"x2'
3 T5




Photometry

Report Summary

Report #
Filename 3352D1F314.ies
Efficiency %


Spacing Criteria @ 0° along
@ 90° across

Candela Distribution




Consult factory for this configuration.

Coefficients of Utilization (%)



Avg. Luminance (cd/m²)




IES files for this and other photometric options can be downloaded online at www.ledalite.com

Additional Information


Mounting

Integrates with most common T-bar ceiling types.



Flat T-Grid

Works with 9/16" and 15/16" flat T-grid ceilings.




Slot T-Grid

Can also be used with slot T-grid ceilings, but it will not sit flush with the bottom of the T-bar.

Ceiling Types

Integrated mounting tabs can be field-adjusted to various T-bar ceiling heights for fastening directly to the T-bar grid and/or tied-off to the building structure.



1" T-bar height
1-1/2" T-bar height
1-11/16" T-bar height

Specifications

Due to continuing product improvements, Ledalite reserves the right to change specifications without notice.

Housing

Die-formed, post-painted, 22 gauge cold-rolled steel. Wire entrances are positioned on the side of the housing to allow easy wiring access for the installer. Multiple wire entrances are available on top or side to allow continuous row mounting of fixtures. Maintenance can be performed from below the ceiling without tools. No hardware is visible.

Weight

Maximum 23 lbs.

Optical System

Optical system consists of highly reflective painted interior reflectors and three flat acrylic lenses with 95% transmittance.

Mounting

Fixture is compatible with most common T-bar ceiling types. Integrated tabs are provided for different T-grid heights.

Works with 9/16" and 15/16" standard T-grid ceiling systems. Can also be used with slot T-grid ceiling systems but fixture will be slightly regressed above the T-bar.

Ballast

Electronic. Supplied with pre-installed ballast disconnect as per national electric codes.

Wiring

Fixtures are factory pre-wired and tested for all circuits and emergency battery packs; all leads pulled to a side access with cover plate. Optional armored cable flex whips are supplied in 6' lengths. Armored cable flex connectors are supplied in 9' lengths for standard master/satellite configurations.

Approvals

Certified to UL & CSA Standards.

Finish

Housing and Frame: Post-painted, high quality powder coat. Available in white.