


Shine™



Recessed

2'x2'

2 TT5 (40W)



Project Name

Spec Type

Notes

Order Guide

Some combinations of product options may not be available. Consult factory for assistance with your specification.


3322			B240	-		-		-		-	
Product Series & Size Shine 2'x2'	Version D1 Standard T-Grid A1 Air Return on Standard T-Grid	Configuration ST Standalone CR Continuous Row	Lamping 2 TT5 (40W)	Housing S Standard (22ga.) N New York (20ga.) C Chicago Plenum	Wiring 1 1 cct 2 2 cct 5 1 cct w/ Battery Pack 7 1 cct Dimming	Voltage 1 120V 2 277V 3 347V	Ballast E Standard Ballast	See details on next page			
				Consult website for complete list of standard wiring options			Consult website for ballast manufacturer information				

Upgrades & Accessories


Please indicate with check mark.

<input type="checkbox"/> Lamps Included	<input type="checkbox"/> Lamps Included & Installed
<input type="checkbox"/> Job Pack	<input type="checkbox"/> Flex Whip
<input type="checkbox"/> Drywall Kit	<p>Can be mounted to wood frame or with hanger wire</p> <p>Wood Frame Hanger Wire</p>
<input type="checkbox"/> Response Daylight	<p>Not available in continuous row</p> <p>For details visit www.ledalite.com/response</p>

Cross Section




Side View



Shine™

Recessed
2'x2'
2 TT5 (40W)



Photometry


Report Summary

Report # 9901677
Filename 3322D1B240.ies
Efficiency 75%

Spacing Criteria 1.23 @ 0° along
1.36 @ 90° across

Candela Distribution

Vertical Angle	Horizontal Angle					Zonal Lumens
	0	22.5	45	67.5	90	
0	1760	1760	1760	1760	1760	171
5	1752	1754	1757	1763	1765	487
15	1686	1699	1721	1755	1764	752
25	1554	1591	1634	1690	1695	918
35	1357	1410	1465	1539	1551	938
45	1089	1146	1217	1315	1306	804
55	780	841	889	992	982	552
65	487	529	546	609	603	273
75	233	260	249	274	262	59
85	44	55	42	45	35	
90	0	0	0	0	0	



Coefficients of Utilization (%)

Ceiling: Wall:	80				70				50				0
	70	50	30	10	70	50	30	10	70	50	30	10	
0 RCR	89	89	89	89	87	87	87	83	83	83	83	75	
1	82	78	75	73	80	77	74	73	71	69	63		
2	75	69	64	60	73	67	63	65	61	57	53		
3	68	60	54	50	66	59	54	57	52	48	45		
4	62	53	47	42	61	53	46	51	45	41	39		
5	57	48	41	36	56	47	41	45	40	36	33		
6	53	43	36	32	51	42	36	41	35	31	29		
7	49	39	32	28	48	38	32	37	32	28	26		
8	46	35	29	25	44	35	29	34	28	25	23		
9	43	33	26	22	41	32	26	31	26	22	20		
10	40	30	24	20	39	30	24	29	24	20	18		

Based on a floor reflectance of 0.2

Avg. Luminance (cd/m²)


Vertical Angle	Horizontal Angle		
	0	45	90
55	3970	4524	4998
65	3364	3771	4165
75	2628	2808	2955
85	1474	1407	1172

IES files for this and other photometric options can be downloaded online at www.ledalite.com

Additional Information


Mounting

Integrates with most common T-bar ceiling types.



Flat T-Grid

Option D1 works with 9/16" and 15/16" flat T-grid ceilings.




Slot T-Grid

D1 can also be used with slot T-grid ceilings, but it will not sit flush with the bottom of the T-bar.


Ceiling Types

Integrated mounting tabs can be field-adjusted to various T-bar ceiling heights for fastening directly to the T-bar grid and/or tied-off to the building structure.



1" T-bar height
1-1/2" T-bar height
1-11/16" T-bar height

Air Return



The air return version features slotted vents along the sides of the fixture. As a result, the installation method of the air return version is different to the standard version, and the fixture cannot be installed in continuous rows.

Specifications

Due to continuing product improvements, Ledalite reserves the right to change specifications without notice.

Housing

Die-formed, post-painted, 22 gauge cold-rolled steel (New York City version is 20 gauge). Wire entrances are positioned on the side of the housing to allow easy wiring access for the installer. Multiple wire entrances are available on top or side to allow continuous row mounting of fixtures. Maintenance can be performed from below the ceiling without tools. No hardware is visible.

Weight

Maximum 23 lbs.

Optical System

Optical system consists of highly reflective painted interior reflectors and three flat acrylic lenses with 95% transmittance.

Mounting

Fixture is compatible with most ceiling types. Option D1 works with 9/16" and 15/16" standard T-grid ceiling systems. D1 can be used with slot T-grid ceiling systems but fixture will be slightly regressed above the T-bar. Integrated tabs are provided for different T-grid heights. Optional drywall kit is available for non-accessible ceilings.

Ballast

Electronic. Supplied with pre-installed ballast disconnects as per national electric codes.

Wiring

Fixtures are factory pre-wired and tested for all circuits and emergency battery packs; all leads pulled to a side access with cover plate. Optional armored cable flex whips are supplied in 6' lengths for 1x4, 2x2 and 2x4 fixtures. Armored cable flex connectors are supplied in 9' lengths for optional master/satellite configurations.

Air Return

Air return option available in 2'x2' and 2'x4' sizes. Perforated air return side rails are finished in black.

Approvals

Certified to UL & CSA Standards. City of Chicago Approved CCEA (housing option C). Designed to comply with NYC code requirements (Housing Option N).

Finish

Housing and Frame: Post-painted, high quality powder coat. Available in white.