

Achieva®



Project Name

Spec Type

Notes

Suspended
Direct/Indirect
1 T5HO



Order Guide

Some combinations of product options may not be available. Consult factory for assistance with your specification.


8816	H01			-		-		-		
Product Series & Type Achieva Direct/Indirect	Lamping 1 T5HO	Lower Optics W White Louver (34*) P Semi-Specular Louver (15*) S Specular Louver (15*) M Semi-Specular VDT Louver (30*) R Specular VDT Louver (30*)	Upper Optics N None D 60% Down Kit G 80% Down Kit J 100% Down Kit U 80% Up Kit	Run Length <i>Enter the total run length in feet (4ft increments)</i>	Wiring 1 1 cct 3 1 cct w/ Emergency cct 5 1 cct w/ Battery Pack 7 1 cct Dimming	Voltage 1 120V 2 277V 3 347V	Ballast E Standard Ballast Consult website for ballast manufacturer information	Color & Finish W Standard White C Factory Color X Custom Color Consult website for color and finish options		
Mounting Hardware										
					Mount Type Consult separate mounting spec sheet for mount type options		Suspension Length <i>Enter distance from ceiling to top of fixture in inches</i>			
		* Number of louver cells per 4ft section See details on reverse		See details on reverse		See details on reverse		Consult website for complete list of standard wiring options		

Upgrades & Accessories


Please indicate with check mark.

Lamps Included Lamps Included and Installed

Lamp Guard
Not available with upper optics option U



Response Daylight (Integrated Controls)
For details visit www.ledalite.com/response



Suspended
Direct/Indirect
1 T5HO



Photometry Optics MJ Semi-Specular VDT Louver w/ 100% Down Kit


Report Summary

Report # 9900399 **Peak Candela Value*** N/A
Filename 8816H01MJ.ies **Peak to Zenith Ratio*** N/A : 1
Efficiency 42.6% * Between 90-180° vertical angle

Meets RP-1-04 recommendations for VDT-Normal spaces

Candela Distribution

Vertical Angle	Horizontal Angle					Zonal Lumens
	0	22.5	45	67.5	90	
0	603	603	603	603	603	
5	616	655	705	723	728	69
15	598	744	874	948	955	240
25	508	711	1037	1314	1383	458
35	446	731	1041	1064	1046	549
45	243	471	570	592	568	398
55	46	96	181	360	462	200
65	10	12	16	59	45	41
75	2	3	3	3	3	3
85	0	0	0	0	0	0
90	0	0	0	0	0	0
95	1	1	1	2	2	0
105	2	2	2	2	3	4
115	2	3	3	4	4	4
125	2	4	4	5	5	4
135	3	5	5	6	6	4
145	3	6	7	8	8	4
155	4	5	9	10	10	4
165	4	4	5	8	9	2
175	4	4	4	4	4	0
180	4	4	4	4	4	



Coefficients of Utilization (%)

Ceiling: Wall:	80				70				50				0				
	70	50	30	10	70	50	30	10	50	30	10	0	70	50	30	10	0
0 RCR	50	50	50	50	49	49	49	46	46	46	42						
1	47	46	44	43	46	45	43	43	42	41	37						
2	44	41	39	37	43	40	38	39	37	36	33						
3	41	37	34	32	40	37	34	35	33	31	29						
4	38	34	31	28	37	33	30	32	30	28	26						
5	35	30	27	25	34	30	27	29	26	24	23						
6	33	28	24	22	32	27	24	27	24	22	21						
7	30	25	22	20	30	25	22	24	21	19	18						
8	28	23	20	18	28	23	20	22	19	18	17						
9	26	21	18	16	26	21	18	20	18	16	15						
10	25	20	16	14	24	19	16	19	16	14	13						

Based on a floor reflectance of 0.2

Avg. Luminance (cd/m²)

Vertical Angle	Horizontal Angle		
	0	45	90
55	654	2572	6566
65	193	309	868
75	63	94	94
85	0	0	0

IES files for this and other photometric options can be downloaded online at www.ledalite.com


Additional Information

Modules

Module length excludes endcaps. Nominal mount spacing for individually mounted modules with fixed position mounts.


Module	Mount Spacing
4ft	4' 0"
8ft	8' 0"
12ft	12' 0"

Endcap




Mounting in Runs

Fixed position mounts supplied standard at ends. Variable position mounts supplied standard at joints. Variable position mounts cannot be located on 4ft modules. Optional variable position mounts at ends available upon request (8ft and 12ft modules only).



Upper Optics

Downlight kits and lamp separators are not recommended with white louvers (lower optics option W), due to potential for excessive louver brightness or shadowing.



Specifications

Due to continuing product improvements, Ledalite reserves the right to change specifications without notice.

Housing

6063 T5 extruded aluminum.

Weight

2.7 lb/ft.

Optical System

Constructed of 96% reflective white steel to produce a direct/indirect distribution. Louvers are available in white blades and aluminum specular or semi-specular blades. White louver blades are spaced 1.3" apart and are 1.1" deep (34 cells per 4ft section). Standard specular and semi-specular louver blades are spaced 3" apart and are 1" deep (15 cells per 4ft section). Specular VDT and semi-specular VDT louver blades are spaced 1.5" apart and are 1" deep (30 cells per 4ft section). Optional field-installable Variable Optics kits provide additional up or downlight as required.

Endcaps

Aluminum die-cast endcaps, baked powder coat finish for color.

Joints

Self-aligning joining system.

Mounting

Fixed position mounts supplied standard at ends. Variable position mounts supplied standard at joints. Variable position mounts can be located on 8ft or 12ft modules within 12" of joint or end. Aircraft cable gripper is tamper-resistant and provides infinite vertical adjustment capability. Aircraft cable, crimp and cable gripper independently tested to meet stringent safety requirements.

Electrical

Factory pre-wired to section ends with quick-wire connectors.

Ballast

Electronic.

Approvals

Certified to UL and CSA standards.

Finish

High-quality powder coat. Available in Ledalite Standard White (textured matte finish), and a selection of other factory and customer-specified colors. Consult factory for details.