




# Recessed

## Shine

20"x4', 4000 lm  
3000/3500/4000K



Project: \_\_\_\_\_  
 Spec Type: \_\_\_\_\_  
 Catalog No: 3354xxxxL8xD \_\_\_\_\_  
 Qty \_\_\_\_\_  
 Line Notes: \_\_\_\_\_

A family of uniformly luminous fixtures, Philips Ledalite Shine recessed delivers outstanding performance for superior energy savings. Available in a wide variety of sizes, Shine is a highly efficient and economical solution for any recessed lighting and energy challenge.

### Ordering guide

Product Type	Version	Configuration	Light Source *	CRI/CCT	Lumens *	Housing	Wiring †	Voltage	Driver
3354	D1	ST	L	8x	D				
Shine 20"x4'	D1 Standard T Grid	ST Standalone	L LED	8C CRI 80 3000K 8B CRI 80 3500K 8A CRI 80 4000K	D 4000 lm C 5200 lm A 6800 lm	S Standard C Chicago Plenum	7 1 cct Dimming N 1 cct Dimming + EM Batt Pack	1 120V 2 277V 3 347V	E Philips Advance 0-10V (1% dim)

\* Nominal values within a range. Consult photometry data for CRI, color temp, lumens & distribution of chosen configuration.  
 † Not all wiring types are available with all configurations. Consult Philips Ledalite for a complete list of available options.

### Upgrades & Accessories Please indicate with check mark.

- Flex Whip (6' length)
- Solid Filler Panel (set of 2)
- Perforated Filler Panel/Air Return (set of 2)

### Integrated Controls Please indicate with check mark.

- Response Daylight Single Zone (DS)



# Shine

20"x4', 4000 lm  
3000/3500/4000K

## Optical System

Optical system consists of highly reflective painted interior reflectors and three flat acrylic lenses.

## Finish

Housing and Frame: Post-painted, high quality powder coat. Available in white.

## Housing

Die-formed, post-painted, 22 gauge cold-rolled steel. Wire entrance is positioned on top and the sides of housing to allow easy wiring access for installation. Access to boards and drivers from below via side lens cavity. T-bar clips built into the luminaire ends for quick and easy installation. Optional perforated or solid filler panels for 20"x48" fixtures to accommodate 60" ceiling grid.

## Weight

Maximum 40lbs

## Optical System

Optical system consists of highly reflective painted interior reflectors and three flat acrylic lenses.

## Electrical

LED boards are easily field replaceable, if required. Fixtures are factory pre-wired and tested for all circuits and emergency battery packs; all leads pulled to a side access with cover plate.

## Standard Driver

Philips Advance Xitanium 0-10V, 1-100%. Class 2 rated output. Consult Philips Ledalite for other available drivers.

## Standard Battery Pack

Philips Bodine, 90 min, 10W, Class 2 rated output. Emergency lumen output = 10W x luminaire efficacy x 1.1. Typical output: 1200lm.

## Lumen Maintenance

LEDs have been tested by the manufacturer in accordance with IESNA LM-80-08. At an ambient temperature of 25°C, the LED lumen maintenance expectation according to IES TM-21-11 is: L80 (12k) >72,000 hrs (Reported methodology).

## Source Color

LEDs rated for color rendering CRI >80, R9 >0 and fixture to fixture color accuracy within 3 SDCM.

## Controls

Available with the following integrated controls: Response daylight sensor (for single zone).

## Mounting

Compatible with 15/16" lay-in acoustical ceilings using exposed grid suspension (NEMA type G). For 9/16" slot T-grid ceilings, fixture will sit 5/16" above bottom of Tee. Integrated tabs are provided for different T-grid heights.

## Wiring

Optional armored cable flex whips are supplied in 6' lengths.

## Approvals

Certified to UL & CSA Standards. City of Chicago Approved CCEA (housing option C).

## Warranty

Five-year luminaire limited warranty including LED boards and driver.

USA: <http://www.usa.lighting.philips.com/support/support/warranty>

Canada: <http://www.lighting.philips.ca/support/support/warranty>


## Environment

Rated for dry & damp locations in operating in ambient temperatures of 25°C. Many luminaire components, such as reflectors, refractors, lenses, and LEDs are made from various types of plastics which can be adversely affected by airborne contaminants. If sulfur based chemicals, petroleum based products, cleaning solutions, or other contaminants are expected in the intended area of use, consult factory for compatibility. Damage caused by sulfur, chlorine, petroleum based solution or other contaminants are not covered under warranty.


Due to continuing product improvements, Philips Ledalite reserves the right to change the specifications without notice.

## Options and Details


### Mounting



### Ceiling types




### Cross Section



# Shine

20"x4', 4000 lm  
3000/3500/4000K

## Photometry @ CRI>80, 3500K



### Candela Distribution

Vertical Angle	Horizontal Angle					Zonal Lumens
	0	22.5	45	67.5	90	
0	1593	1593	1593	1593	1593	0
5	1577	1581	1576	1584	1581	150
15	1486	1510	1500	1526	1509	425
25	1339	1368	1352	1377	1351	626
35	1141	1176	1153	1166	1138	724
45	902	940	914	925	899	711
55	666	702	669	681	655	605
65	437	459	424	423	410	429
75	214	230	199	207	185	224
85	37	48	28	35	24	48
90	0	0	0	0	0	0
95	0	0	0	0	0	0
105	0	0	0	0	0	0
115	0	0	0	0	0	0
125	0	0	0	0	0	0
135	0	0	0	0	0	0
145	0	0	0	0	0	0
155	0	0	0	0	0	0
165	0	0	0	0	0	0
175	0	0	0	0	0	0
180	0	0	0	0	0	0

Fixture photometry has been conducted in accordance with IESNA LM-79-08

IES files for this and other photometric options can be downloaded online at [www.lightingproducts.philips.com](http://www.lightingproducts.philips.com)

### Coefficients of Utilization (%)

RCR	Ceiling												
	70	50	30	10	70	50	30	10	70	50	30	10	0
0	119	119	119	119	116	116	116	111	111	111	111	100	0
1	109	105	101	97	107	103	99	98	95	93	85	85	0
2	100	92	86	80	97	90	84	87	82	77	72	72	0
3	91	81	73	67	89	80	72	77	71	65	61	61	0
4	84	72	64	57	82	71	63	69	62	56	53	53	0
5	77	65	56	50	75	64	56	62	54	49	46	46	0
6	72	59	50	44	70	58	49	56	49	43	40	40	0
7	66	53	45	39	65	52	44	51	44	38	36	36	0
8	62	49	40	35	60	48	40	47	40	34	32	32	0
9	58	45	37	31	57	44	37	43	36	31	29	29	0
10	54	41	34	28	53	41	33	40	33	28	26	26	0

### Avg. Luminance (cd/m2)

Vertical Angle	Horizontal Angle		
	0	45	90
55	2029	2040	1997
65	1808	1755	1695
75	1448	1346	1250
85	742	556	473

### Distribution Summary

Hemisphere	0% Up / 100% Down
Spacing Along (0°)	1.17
Spacing Across (90°)	1.17

# Shine

20"x4', 4000 lm  
3000/3500/4000K

## Optical Performance

Flux (lm)	3936	3942	3736
Efficacy (lm/W)	118.9	118.4	112.9
Power (W)	33.1	33.3	33.1
CCT (K)	3900	3348	2995
CRI	82	82	81
R9	11	6	3
x	0.3865	0.4162	0.4397
y	0.3849	0.4002	0.4092
Duv	0.0020	0.0020	0.0020

## Electrical Performance @ CRI>80, 3500K

Input Voltage	120V	277V	347V
Input Power	33.3W	32.7W	32.7W
Input Current	0.28A	0.12A	0.10A
Power Factor	0.998	0.974	0.962
Total Harm. Distortion	5.4%	12.3%	10.0%

Tested values – contact technical support for rated values. Off-state power zero unless certain controls are specified.

