


Shine™



Recessed

2'x2'

2 TT5 (25W)



Project Name

Spec Type

Notes

Order Guide

Some combinations of product options may not be available. Consult factory for assistance with your specification.

3322			B225	-		-		-		-	
Product Series & Size	Version	Configuration	Lamping	Housing	Wiring	Voltage	Ballast				
Shine 2'x2'	D1 Standard T-Grid A1 Air Return on Standard T-Grid	ST Standalone CR Continuous Row	2 TT5 (25W)	S Standard (22ga.) C Chicago Plenum	1 1 cct 2 2 cct 7 1 cct Dimming	1 120V 2 277V 3 347V	E Standard Ballast				
	See details on next page				Consult website for complete list of standard wiring options		Consult website for ballast manufacturer information				


Upgrades & Accessories

Please indicate with check mark.


<input type="checkbox"/> Lamps Included	<input type="checkbox"/> Lamps Included & Installed
<input type="checkbox"/> Job Pack	<input type="checkbox"/> Flex Whip
<input type="checkbox"/> Drywall Kit	<p>Can be mounted to wood frame or with hanger wire</p>
<input type="checkbox"/> Response Daylight	

For details visit www.ledalite.com/response

Cross Section




Side View



Shine™

Recessed
2'x2'
2 TT5 (25W)



Photometry


Report Summary

Report # 9901747
Filename 3322D1B225.ies
Efficiency 86.5%

Spacing Criteria 1.18 @ 0° along
1.33 @ 90° across

Candela Distribution

Vertical Angle	Horizontal Angle					Zonal Lumens
	0	22.5	45	67.5	90	
0	1718	1718	1718	1718	1718	167
5	1698	1705	1709	1718	1721	471
15	1619	1639	1667	1700	1706	718
25	1471	1512	1564	1612	1620	862
35	1255	1318	1374	1460	1465	861
45	983	1060	1117	1210	1216	713
55	690	745	792	882	867	468
65	409	458	457	524	499	209
75	180	202	184	209	191	30
85	20	22	12	18	14	
90	0	0	0	0	0	



Coefficients of Utilization (%)

Ceiling: Wall:	80				70				50				0				
	70	50	30	10	70	50	30	10	50	30	10	0	70	50	30	10	0
0 RCR	103	103	103	103	100	100	100	96	96	96	86	86	86	86	86	86	86
1	95	91	88	85	92	89	86	85	83	81	74	74	74	74	74	74	74
2	87	80	74	70	84	78	73	75	71	67	63	63	63	63	63	63	63
3	79	71	64	59	77	69	63	67	61	57	53	53	53	53	53	53	53
4	73	63	56	50	71	62	55	60	54	49	46	46	46	46	46	46	46
5	67	56	49	43	65	55	48	53	47	42	40	40	40	40	40	40	40
6	62	51	43	38	60	50	43	48	42	37	35	35	35	35	35	35	35
7	57	46	39	33	56	45	38	44	38	33	31	31	31	31	31	31	31
8	53	42	35	30	52	41	34	40	34	30	28	28	28	28	28	28	28
9	50	38	32	27	49	38	31	37	31	27	25	25	25	25	25	25	25
10	47	35	29	24	46	35	29	34	28	24	22	22	22	22	22	22	22

Based on a floor reflectance of 0.2

Avg. Luminance (cd/m²)


Vertical Angle	Horizontal Angle		
	0	45	90
55	3512	4031	4413
65	2825	3157	3447
75	2030	2075	2154
85	670	402	469

IES files for this and other photometric options can be downloaded online at www.ledalite.com

Additional Information


Mounting

Integrates with most common T-bar ceiling types.



Flat T-Grid

Option D1 works with 9/16" and 15/16" flat T-grid ceilings.




Slot T-Grid

D1 can also be used with slot T-grid ceilings, but it will not sit flush with the bottom of the T-bar.


Ceiling Types

Integrated mounting tabs can be field-adjusted to various T-bar ceiling heights for fastening directly to the T-bar grid and/or tied-off to the building structure.



1" T-bar height
1-1/2" T-bar height
1-11/16" T-bar height

Air Return



The air return version features slotted vents along the sides of the fixture. As a result, the installation method of the air return version is different to the standard version, and the fixture cannot be installed in continuous rows.

Specifications

Due to continuing product improvements, Ledalite reserves the right to change specifications without notice.

Housing

Die-formed, post-painted, 22 gauge cold-rolled steel (New York City version is 20 gauge). Wire entrances are positioned on the side of the housing to allow easy wiring access for the installer. Multiple wire entrances are available on top or side to allow continuous row mounting of fixtures. Maintenance can be performed from below the ceiling without tools. No hardware is visible.

Weight

Maximum 23 lbs.

Optical System

Optical system consists of highly reflective painted interior reflectors and three flat acrylic lenses with 95% transmittance.

Mounting

Fixture is compatible with most ceiling types. Option D1 works with 9/16" and 15/16" standard T-grid ceiling systems. D1 can be used with slot T-grid ceiling systems but fixture will be slightly regressed above the T-bar. Integrated tabs are provided for different T-grid heights. Optional drywall kit is available for non-accessible ceilings.

Ballast

Electronic. Supplied with pre-installed ballast disconnects as per national electric codes.

Wiring

Fixtures are factory pre-wired and tested for all circuits and emergency battery packs; all leads pulled to a side access with cover plate. Optional armored cable flex whips are supplied in 6' lengths for 1x4, 2x2 and 2x4 fixtures. Armored cable flex connectors are supplied in 9' lengths for optional master/satellite configurations.

Air Return

Air return option available in 2'x2' and 2'x4' sizes. Perforated air return side rails are finished in black.

Approvals

Certified to UL & CSA Standards. City of Chicago Approved CCEA (housing option C). Designed to comply with NYC code requirements (Housing Option N).

Finish

Housing and Frame: Post-painted, high quality powder coat. Available in white.