

PHILIPS
LEDALITE

Recessed

VersaForm LED



Unlock your **vision**

Harmonious style and uncompromising quality combine seamlessly in the Philips Ledalite VersaForm LED recessed luminaire family.



VersaForm LED

The VersaForm recessed luminaires were specifically designed to blend high performance LED technology with versatile options to suit any area. You can create a solution specific to your style with VersaForm's wide palette of sizes, lumen packages, color temperatures, color renderings, housings, mountings, with optional controls and sensors. This allows you to enjoy the latest LED energy efficiencies in concert with your unique style, and as your needs evolve, it's simple to change or upgrade with our unique detachable light engine.

Specification guide

example: 4122D2STL8CE51EDS

Series		Type		Lumen Package			Body	Electrical			
Family	Size	Version	Configuration	Source	CRI/CCT	Lumens*	Housing	Wiring	Voltage	Driver	Integ. Controls
41	<input type="checkbox"/>	<input type="checkbox"/>	ST	L	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	E	<input type="checkbox"/>
41 VersaForm LED	14 1'x4'	D1 Standard T-Grid D2 Tegular/Slot T-Grid A1 Air Return/Std. T-Grid A2 Air Return/Slot T-Grid S1 Surface Mount	ST Standalone	L LED	8A 80/4000K 8B 80/3500K 8C 80/3000K 9B 90/3500K	E 3000lm D 4000lm C 5200lm A 6800lm	S Standard C Chicago	1 1 cct 5 1 cct w/battery pack 7 1 cct w/dimming (0-10V)	1 120V 2 277V 3 347V	E Standard	DS Response Daylight Sensor DO Actilume Occupancy Sensor
	22 2'x2'										


Features

- Efficacies up to 115lm/w.
- Batwing distribution means wide row spacing, fewer luminaires and exceptionally low energy density (W/sqft).
- Balanced Brightness with glare control
- Light Engine separate unit enabling easy maintenance and upgradability.


Dimensions
4' & 2' Lengths

Dimensions
1' & 2' Widths


Side View




Cross Section



Cross Section



Side View



*Nominal output within a range, consult spec sheets for exact lumen output for each configuration.

Some options may not be available for each configuration. Consult factory for full list of available options.

©2014 Koninklijke Philips N.V. All rights reserved. Philips reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

PLe-1405BN 08/14 philips.com/luminaires



Philips Lighting, North America Corporation
200 Franklin Square Drive, Somerset, NJ 08873 • Tel. 855-486-2216

Imported by: Philips Lighting,
A division of Philips Electronics Ltd.
281 Hillmount Rd, Markham, ON, Canada L6C 2S3 • Tel. 800-668-9008